

AMENDMENTS TO THE SPECIFICATION

Please replace paragraph [0030] with the following amended paragraph:

[0030] Main support 302 includes a semicircular bottom portion 324 with an opening 328 for receiving third link pin 146 therethrough, a main body portion 332, a motor interface portion 336, and main support cover 303. Main body portion 332 includes a gear cavity 340 for housing first gear 304 and intermediate gear 316, a gear cavity 344 for housing intermediate gears 318 and 320, and a gear cavity 348 for housing intermediate gear 322. Gear cavity 340 includes a pivot shaft opening 352 for supporting a lower end of pivot shaft 306, gear cavity 344 includes a pivot shaft opening 356 for supporting a lower end of pivot shaft 321, and gear cavity 348 includes a pivot shaft opening 360 for supporting a lower end of pivot shaft 312. A pivot shaft opening 362 is formed in main support cover ~~362~~ 303 supporting an upper end of pivot shaft 321. A bushing 364 is disposed in gear cavity 348 between intermediate gear 322 and main body portion 332 to stabilize intermediate gear 322. Motor interface portion 336 is provided for stably interfacing motor 206 with main support 302 and includes a drive shaft receiving member ~~370~~ 366 with a drive shaft receiving opening ~~374~~ 368 for receiving drive shaft 222 therethrough so that motor shaft drive gear 230 may engage first gear 304.